

NetLink Category PDB-IEC16-4V 20 Way Vertical Slimline 16 x C13 and 4 C19 IEC sockets with 20A Commando Plug 0U Power Distribution Unit

FEATURES

16 x C13 Socket Outputs

4 x C19 Outputs

20Amp IND309 Commando

Slim line style IEC for side space saving

16Amp IND309 Commando plug Power Input on Lead Input Connector 16 Amp Rated

SPECIFICATION

Manufactured using C13 /C19 sockets

Manufactured to BS5733, with UL, CSA & VDE approved components.

Current rating 20 A



SPECIFICATION

INPUT Input frequency 50/60 Hz
Acceptable Input Voltage 220 - 240VAC
Number of Power Cords 1

Load Capacity 3600VA
Maximum Input Current 16A
Maximum Line Current 16A

PHYSICAL Maximum Height 1800MM, 180.0CM

Maximum Width 55MM, 5.5CM

Maximum Depth 56MM, 5.6CM

Net Weight 6.32KG

Color Black

Environmental Operating Temperature -5 - 45 °C

Operating Relative Humidity - 95%

Storage Temperature - 25 - 65 °C

Storage Relative Humidity 5 - 95%

WARRANTY

Warranty 5 Year

XCELL 0U Vertical C13 Socket PDU will be providing reliable and secure connection to the Data Center applications, Server or Network Racks installation. Robust construction with External and internal cabling High quality, CNC built and Manufactured in Sri Lanka