

XCELL NetLink 10/100/1000 Mbps Fiber Optic Media Converter – SFP, SM/MM, 230V

(Part No: XL-MC-1G-SFP-SMMM)

The Xcell Netlink Fiber Optic Media Converter provides reliable 10/100/1000 Mbps Ethernet connectivity over Single-Mode or Multi-Mode optical fiber using an SFP module. The RJ45 port supports automatic speed negotiation, while the SFP optical interface supports 100/1000 Mbps. LED indicators provide quick monitoring of power and link/activity status.



Features

- Plug-and-play operation with high performance and low power consumption.
- Supports 10/100/1000 Mbps Ethernet with automatic speed negotiation.
- SFP-compatible optical interface supporting 100/1000 Mbps transmission.
- Supports Single-Mode (SM) and Multi-Mode (MM) fiber depending on the selected SFP module.
- RJ45 electrical interface with Auto-Negotiation and automatic MDI/MDI-X crossover.
- Store-and-forward switching architecture.
- Transmission distance depends on the selected SFP module.
- Status LEDs for PWR, TX Link/ACT, FX Link/ACT, 100M and 1000M.
- DC powered operation.

Applications

Suitable for Ethernet-to-fiber connectivity in telecommunications, enterprise networks, CCTV/network infrastructure, building networks and other applications requiring long-distance single-mode fiber transmission.

Technical Specifications	
Brand	Xcell Netlink
Product Name	10/100/1000 Mbps Fiber Optic Media Converter - SFP, SM/MM, 230V
Standards	IEEE 802.3i IEEE 802.3u IEEE 802.3x Flow Control IEEE 802.1af DTE Power via MDI IEEE 802.3z / IEEE 802.3ab
Optical Fiber	Single Mode (SM) / Multi Mode (MM), depending on SFP module
Wavelength	Depends on selected SFP module
Optical Port	1 × Fiber Port, SC
Ethernet Port	1 × RJ45
Ethernet Speed	10/100/1000 Mbps
Transmission Distance	depends on selected SFP module; RJ45: up to 100 m
Network Media	10BASE-T: Cat3/4/5 UTP ≤100 m; 100BASE-TX: Cat5 or above UTP ≤100 m
Forwarding Mode	Store-and-forward
Power Supply	DC 5 V / 1 A
Operating Temperature	-20 °C~75 °C
Storage Temperature	-40 °C~85 °C
Relative Humidity	0-95% RH, non-condensing
Dimensions	6.9 cm × 3.7 cm × 2.3 cm

Warranty

Warranty	180 days
----------	----------