

Xcell NetLink Category 6

24 Port, UTP, Patch Panel, Unloaded

- Category 6 performance
- 24 Ports
- UTP construction
- RJ45 interface
- 1U Rack-mount format



MAIN SPECIFICATIONS

Range of products	NetLink
Product / component type	Patch Panel
Cable shielding type	UTP
Communication network category	6
Number of ports	24

TECHNICAL SPECIFICATIONS

Connector type	RJ45
Minimum number of matings	750 cycles
Rated current [In]	1.5 A
Insulation resistance	≥ 500 mOhm at 500 V DC
Contact resistance	20 mOhm
Panel material	Steel, powder coated
Contact material	Phosphor bronze, 50 micro-inches gold over 100 micro-inches nickel
Width	482.6 mm
Height	44.2 mm
Rack unit	1U

STANDARDS, PACKING & WARRANTY

Standards	ANSI/TIA-568-C.2; ISO/IEC 11801 class E; EIA/TIA TSB 40 A
Product certification	UL / ETL Verified
Environmental characteristic	Flame retardant
Unit type / units per package	PCE / 1
Package dimensions (H x W x L)	8 cm x 10 cm x 52 cm
Package weight	750 g
Warranty	1 Year

ORDER INFORMATION

Product Description	Part No
Xcell NetLink UTP CAT 6 Patch Panel 24 Port, 1U	XLPTP-BLK24H01